

LINEAR PULSED POWER AMPLIFIER

Model – MP300500M593050

General Description:

Elite RF's **MP Series** amplifier is a narrowband power amplifier designed for Pulsed signals fabricated on GaN on SiC process and can operate up to **500 MHz**. These amplifiers offer high power density, low thermal resistance, and narrowband performance. They can be widely used for military and commercial applications.

Like all Elite RF amplifiers, this product comes with an industry leading **5-year warranty**.



Features

Pulsed operation
High Pk. Output Power
High Gain
High Reverse Isolation
Built-in Protection
Enable/Disable input (ground to disable)

Indicator options

DC Power
Temp Fault

Protections

Thermal Overload
Over Voltage
Reverse Polarity

ELECTRICAL SPECIFICATIONS

Parameter	Symbol	Min	Typ	Max	Unit
Frequency Range	BW	300		500	MHz
Output Power Pk	Psat		700		Watt
Duty Cycle	Dc		1	2	%
Small Signal Gain	Gp		32		dB
Gain Flatness	Delta Gp 1		+/- 2		dB
Input VSWR	S11		2:1		Ratio
Pulse width	Pw		50	200	uS
Harmonics	H		-20		dBc
Spurious Signals	Spur		-60		dBc
Operating Voltage	VDC	49	50	51	VDC
Average Current at 700 watts @ 1% DC	Current		1		Amps
Class of Operation	C		AB		Class
Noise Figure	NF		N/A		dB
Large Signal Gain	Lsg		30		dB
Max Load VSWR @ 700 watts	ML		10:1		Ratio

ENVIRONMENTAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Operating Case Temperature	Tc	-20		+60	Deg. C
Storage Temperature	Tstg	-40		+85	Deg. C
Relative Humidity (non-condensing)	RH			95	%
Altitude	ALT			10,000	Feet
Vibration/Shock	VI /SH				Normal Truck Transport

MECHANICAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Dimensions	Dim		10 x 10 x 2.0		Inches
Weight	Wt.		4		lbs.
Connectors In/Out	RF Conn		SMA/SMA		-
Cooling	Th		Heat sink required		-

OPTIONS

Parameter	Add suffix to part number
Heat sink and fans	- H
Isolator with forward and reverse voltage outputs	N/A
TTL Input Trigger	- T

