

# LINEAR WIDEBAND POWER AMPLIFIER

**Model – AB002250M5750AC**

## General Description:

Elite RF's AB Series amplifier is a wideband power amplifier designed for CW signals fabricated on LDMOS process and can operate up to **250 MHz**. These amplifiers offer high power density, low thermal resistance, and wideband performance. They can be widely used for military and commercial applications.

Like all Elite RF amplifiers, this product comes with an industry leading warranty.



## Features

- Wide Freq. Range
- High Output Power
- High Gain
- High Reverse Isolation
- Built-in Protection

## Protections

- Thermal Overload
- Over Voltage
- High VSWR

## ELECTRICAL SPECIFICATIONS

Parameter	Symbol	Min	Typ	Max	Unit
Frequency Range	BW	2		250	MHz
Output Power CW	Psat		500		Watt
Output Power at 1 dB Compression	P1dB		200		Watt
Small Signal Gain	Gp		50		dB
Gain Flatness	Delta Gp 1		+/- 2		dB
Input VSWR	S11		2:1		Ratio
IMD	IP3		N/A		dBm
Harmonics	H		-20		dBc
Spurious Signals	Spur		-60		dBc
Operating Voltage	Opv	100	120	240	VAC
AC Power at 500 watts	Pd		1000		Watt
Class of Operation	C		AB		Class
Noise Figure	NF		N/A		dB
Large Signal Gain	Lsg		48		dB
Max Load VSWR @ 500 Watts	ML		6: 1		Ratio

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Operating Temperature	Tc	0		+50	Deg. C
Storage Temperature	Tstg	-40		+85	Deg. C
Relative Humidity (non-condensing)	RH			95	%
Altitude	ALT			10,000	Feet
Vibration/Shock	VI /SH		Normal Truck Transport		




## MECHANICAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Dimensions	Dim		19 x 15 x 5.25		Inches
Weight	Wt.		25		lbs.
Connectors In/Out	RF Conn		N-Type		-
Cooling	Th		Forced air cooling		-

## OPTIONS

Parameter	Add suffix to part number
Heat sink and fans	N/A
Isolator with forward and reverse voltage outputs	N/A
TTL Input Trigger	N/A

## Mechanical Drawings



Elite RF LLC

1700 Tower Dr, Hanover Park, IL 60133, USA  
Call us for customer service/technical support at: 847-592-6350  
Email: sales@eliterf.com Web: www.eliterfllc.com

Rev 1 02/08/2023:  
Specifications subject to change,  
consult sales for latest information  
ECCN: EAR99  
USHTS: 8541290075