

LINEAR WIDEBAND POWER AMPLIFIER

Model – MB6.0018G454822

General Description:

Elite RF's MB Series amplifier is a wideband power amplifier designed for CW signals fabricated on GaN on SiC process and can operate up to **18.0 GHz**. These amplifiers offer high power density, low thermal resistance, and wideband performance. They can be widely used for military and commercial applications.

Like all Elite RF amplifiers, this product comes with an industry leading warranty.



Features	Indicator options	Protections
Wide Freq. Range High Output Power High Gain High Reverse Isolation Built-in Protection	DC Power Temp Fault	Thermal Overload Over Voltage Reverse Polarity

ELECTRICAL SPECIFICATIONS

Parameter	Symbol	Min	Typ	Max	Unit
Frequency Range	BW	6000		18000	MHz
Output Power CW	Psat		30		Watt
Output Power at 1 dB Compression Small	P1dB		10		Watt
Signal Gain	Gp		48		dB
Gain Flatness	Delta Gp 1		+/- 3		dB
Input VSWR	S11		2:1		Ratio
IMD @ 12 GHz @ 1 watt one / 1 MHz spacing	IP3		45		dBm
Harmonics	H		-20		dBc
Spurious Signals	Spur		-50		dBc
Operating Voltage	VDC	19	20	21	VDC
Current at 30 watts	Current		6.0		Amps
Class of Operation	C		AB		Class
Noise Figure	NF		5		dB
Large Signal Gain	Lsg		46		dB
Max Load VSWR @ 30 Watts	ML		6:1		Ratio

ENVIRONMENTAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Operating Case Temperature	Tc	-20		+80	Deg. C
Storage Temperature	Tstg	-40		+85	Deg. C
Relative Humidity (non-condensing)	RH			95	%
Altitude	ALT			10,000	Feet
Vibration/Shock	VI /SH				Normal Truck Transport




MECHANICAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Dimensions	Dim		6.0 x 4.0 x 1.0		Inches
Weight	Wt.		1		lbs.
Connectors In/Out	RF Conn		SMA/SMA		-
Cooling	Th		Heat sink required		-

OPTIONS

Parameter	Add suffix to part number
Heat sink and fans	- H
Enable/Disable	- E
TTL Input Trigger	- T

Mechanical Drawings



Elite RF LLC

1700 Tower Drive, Hanover, IL. 60133
Call us for customer service/technical support at: 847-592-6350 Order
or email us on-line at www.eliterfllc.com

Rev04/8/2022:
Specifications subject to change,
consult sales for latest information

Product Compliance:
ECCN: 3A001.b.4..b.4
USHTS: 8543.70.8000