

LINEAR WIDEBAND POWER AMPLIFIER

Model – MB.502.5G474850



50 watts 500 to 2500 MHz 50 VDC

General Description:

Elite RF's MB Series amplifier is a wideband power amplifier designed for CW signals fabricated on GaN on SiC process and can operate up to **2.5 GHz**. These amplifiers offer high power density, low thermal resistance, and wideband performance. They can be widely used for military and commercial applications.

Like all Elite RF amplifiers, this product comes with an industry leading warranty.

Features

Wide Freq. Range
High Output Power
High Gain
High Reverse Isolation
Built-in Protection
Enable/Disable input (ground to disable)

Protections

Thermal Overload
Reverse Polarity

ELECTRICAL SPECIFICATIONS

Parameter	Symbol	Min	Typ	Max	Unit
Frequency Range	BW	500		2500	MHz
Output Power CW	Psat		50		Watt
Output Power at 1 dB Compression Small Signal	P1dB		25		Watt
Gain	Gp		48		dB
Gain Flatness	Delta Gp 1		+/- 3		dB
Input VSWR	S11		2:1		Ratio
IMD @ 2 GHz @ 1 watt/tone @ 1 MHz spacing	IP3		53		dBm
Harmonics	H		-20		dBc
Spurious Signals	Spur		-60		dBc
Operating Voltage	VDC	48	50	51	VDC
Current at 50 watts	Current		3		Amps
Class of Operation	C		AB		Class
Noise Figure	NF		5		dB
Large Signal Gain	Lsg		46		dB
Max Load VSWR @ 50 Watts	ML		6:1		Ratio

ENVIRONMENTAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Operating Case Temperature	Tc	-20		+60	Deg. C
Storage Temperature	Tstg	-40		+85	Deg. C
Relative Humidity (non-condensing)	RH			95	%
Altitude	ALT			10,000	Feet
Vibration/Shock	VI /SH		Normal Truck Transport		


MECHANICAL CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Dimensions	Dim		7.88 x 2.78 x 1.06		Inches
Weight	Wt.		2		lbs
Connectors In/Out	RF Conn		SMA/SMA		-
Cooling	Th		Heat sink required		-

OPTIONS



Parameter	Add suffix to part number
Heat sink and fans	- H
Isolator with forward and reverse voltage outputs	N/A
TTL Input Trigger	- T

Mechanical Drawings



D-Sub Connections

Pin 1-4: 50 VDC
Pin 5: Disable "Ground to disable"
Pin 6-9: Ground



Elite RF LLC
1700 Tower Dr, Hanover Park, IL 60133, USA
Call us for customer service/technical support at: 847-592-6350
Email: sales@eliterf.com Web: www.eliterfllc.com

Rev 4 01/03/2025:
Specifications subject to change, consult
sales for latest information

USHTS: 8543.70.8000
ECCN: EAR99